

"1+" or "3"

Notification No.: 1008

Test Report No.: 28210310 001

Order No.: 93356030

Page 1 / 2

Harmonised standard: EN 50575:2014 + A1:2016

Classification standard: EN 13501-6:2014

Throughout this report a comma is used as the decimal separator.

Abbreviations: ok / P = passed  
fail / F = failed

data / D = publication of data

[www.tuv.hu](http://www.tuv.hu)

## EN 60332-1-2

| Clause | Requirement + Test | Result - Remark | Verdict |
|--------|--------------------|-----------------|---------|
|--------|--------------------|-----------------|---------|

## ZTT GYFJH-2F 7.0mm (ZTT 0959)

**5 Procedure**

Sample length (600 ± 25 mm).....: 615

**P**

Approx. outer diameter (mm) : 7.0

**6 Evaluation of test results**

Not damaged area from lower edge of the top support (min. 50 mm) ..... 366

**P**

No. of samples: 1

Ambient temperature: 26,5 °C

Date of test: 2017.03.07

## Photo documentation

Before test

After test

## Measuring equipment list

| Device          | Manufacturer | Type   | Identification No. | Next calibration |
|-----------------|--------------|--------|--------------------|------------------|
| Measuring tape  | Stabila      | BM 30W | 503509             | 2019.09.21.      |
| Stop-watch      | Helvetia     | S001   | 502911             | 2017.10.25.      |
| Digital caliper | Mitutoyo     | CD-15R | 0556014003         | 2018.01.03       |
|                 |              |        |                    |                  |
|                 |              |        |                    |                  |
|                 |              |        |                    |                  |

-END OF TEST REPORT-